

3C Series Ultra-Thin Power Supply



PRODUCT FEATURES



- ▶ Full range AC voltage input
- ▶ The efficiency reaches 88% at full load (230 V)
- ▶ LED start indicator light
- ▶ Low standby power consumption below 0.2W
- ▶ Protection type: short circuit protection/overload protection/overvoltage protection
- ▶ The working temperature can reach up to 90°C
- ▶ Natural air cooling
- ▶ Small size, aluminum heat dissipation shell
- ▶ 100% ambient temperature 50% full load aging test
- ▶ Can be operated at an altitude of 2000 kilometers
- ▶ 3C, CE, ROHS FCC and other certifications.
- ▶ Output below 5V (including 5V) is synchronous rectification mode

USAGE SCENARIO

- ▶ LED light strips, lightbox advertisements, illuminated signage, lighting equipment, etc

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
3C-60	60W	85-264VAC	12V / 24V	5 A / 2.5A	88%	148*35*22
3C-100	100W	85-264VAC	12V / 24V	8.3A / 4.2A	88%	150*48*22
3C-150	150W	85-264VAC	12V / 24V	12.5A / 6.25A	88%	183*48*22
3C-200	200W	85-264VAC	12V / 24V	16.6A / 8.4A	88%	190*48*22
3C-300	300W	85-264VAC	12V / 24V	25A / 12.5A	88%	238*48*22

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE



HC Series Ultra-Thin Power Supply



PRODUCT FEATURES



- ▶ Full range AC voltage input
- ▶ The efficiency reaches 88% at full load (230 V)
- ▶ LED start indicator light
- ▶ Low standby power consumption below 0.2W
- ▶ Protection type: short circuit protection/overload protection/overvoltage protection
- ▶ The working temperature can reach up to 70°C
- ▶ Natural air cooling
- ▶ Small size, aluminum heat dissipation shell
- ▶ 100% ambient temperature 50% full load aging test
- ▶ Can be operated at an altitude of 2000 kilometers
- ▶ CE, ROHS FCC and other certifications.
- ▶ Output below 5V (including 5V) is synchronous rectification mode

USAGE SCENARIO

- ▶ LED light strips, lightbox advertisements, illuminated signage, lighting equipment, etc

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
HC-24	24W	180-264VAC	12V / 24V	2 A / 1A	88%	125*113.5*32
HC-36	36W	180-264VAC	12V / 24V	3A / 1.5A	88%	125*113.5*40
HC-48	48W	180-264VAC	12V / 24V	4A / 2A	88%	125*113*63
HC-60	60W	180-264VAC	12V / 24V	5A / 2.5A	88%	128*125*85

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE

