



S Series CAN Communication Charging Module



PRODUCT FEATURES

- DCDC adopts half bridge, full bridge LLC and other schemes
- The product has CAN communication capability
- Small size, light weight, generous appearance
- Easy to install, user-friendly, and maintain
- Output integrated 12VBMMS auxiliary source, integrated output reactor, integrated output fuse
- Input sampling three-phase four wire system, wide voltage input; Suitable for various input voltage ranges worldwide
- Has good safety, high reliability, high efficiency, and good compatibility
- Supports parallel operation with no loss of parallel power, ensuring high efficiency and stability

USAGE SCENARIO

- New energy pure electric forklift AGV, Intelligent charging of lithium and lead-acid battery packs for sightseeing vehicles, ships, battery swapping cabinets, communication, power equipment, etc

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	DC VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
S3200-24100	3200W	90Vac to 265Vac 47Hz-63Hz	0V-34V	100A	93%	273*102*83
S3200-24100-K	3200W	90Vac to 265Vac 47Hz-63Hz	0V-34V	100A	93%	273*102*83
S3200-24100-B	3200W	90Vac to 265Vac 47Hz-63Hz	0V-34V	100A	93%	273*102*83
S3200-24100-KB	3200W	90Vac to 265Vac 47Hz-63Hz	0V-34V	100A	93%	273*102*83
S3200-9630-K	3200W	90Vac to 265Vac 47Hz-63Hz	0V-68V	60±0.6A	94%	273*102*83
S3200-96300	3200W	90Vac to 265Vac 47Hz-63Hz	0V-68V	60±0.6A	94%	273*102*83
S3200-4860	3200W	90Vac to 265Vac 47Hz-63Hz	0V-220V	30±0.3A	94%	273*102*83
S3200-4860-K	3200W	90Vac to 265Vac 47Hz-63Hz	0V-220V	30±0.3A	94%	273*102*83
S3200-14420	3200W	90Vac to 265Vac 47Hz-63Hz	0V-200V	100A	93%	273*102*83
S3200-14420K	3200W	90Vac to 265Vac 47Hz-63Hz	0V-200V	20A	94%	273*102*83
S3200-3308	3200W	90Vac to 265Vac 47Hz-63Hz	200V-450V	0.3A-8A	93%	273*102*83

The final parameters and specifications shall be subject to the Product Specification provided by our company



PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	DC VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
S3200-500	3200W	180Vac to 265Vac 47Hz-63Hz	150V-750V	100a	93%	273*102*83
S3000S-24100	3000W	180Vac to 265Vac 47Hz-63Hz	16V-32V	100A±1A	93%	326*128*64
S3000S-4860	3000W	180Vac to 265Vac 47Hz-63Hz	32V-64V	40A	93%	326*128*64
S6000T-48100	6000W	320Vac to 440Vac 47Hz-63Hz	32V-64V	80A	94.5%	346*188*68
S6000T-8080	6000W	320Vac to 440Vac 47Hz-63Hz	48V-100V	100A±1A	94%	346*188*68
S600T-14440	6000W	320Vac to 440Vac 47Hz-63Hz	96V-200V	60A	94%	346*188*68
S10KT-100100	10000W	260Vac to 520Vac 47Hz-63Hz	30V-120V	100A±1A	95%	383*212*70

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE

