



Dual Group Switch Power Supply



PRODUCT FEATURES

- ▶ Full range AC voltage input
- ▶ The efficiency reaches 88% at full load (230 V)
- ▶ LED start indicator
- ▶ Low standby power consumption, less than 0.3W
- ▶ Protection type: short circuit protection/overload protection/overvoltage protection
- ▶ The working temperature can be as high as 70°C
- ▶ Natural air cooling/ Fan Cooling
- ▶ Small size, aluminum cooling shell
- ▶ Full load aging test at 100% ambient temperature of 50°C
- ▶ Can be operated at an altitude of 2000 kilometers
- ▶ CE, ROHS FCC and other certifications.
- ▶ The output below 5V (including 5V) is synchronous

USAGE SCENARIO

- ▶ Electronic/scientific research instruments, industrial control equipment, camera monitoring equipment, medical equipment, lighting equipment, automation equipment, etc

PRODUCT SELECTION TABLE

| MODEL | POWER | INPUT VOLTAGE RANGE | OUTPUT VOLTAGE | OUTPUT CURRENT | EFFCY | SIZE(L*W*H)MM |
|-------|-------|--------------------------|----------------|----------------|-------|---------------|
| D-30A | 30W | 90~132VAC 180~264VAC | (5V, 12V) | (4A, 1A) | 88% | 129*98*38 |
| D-30B | 30W | 90~132VAC 180~264VAC | (5V, 24V) | (2.2A, 1A) | 88% | 129*98*38 |
| D-30C | 30W | 90~132VAC 180~264VAC | (12V, 24V) | (1A, 0.5A) | 88% | 129*98*38 |
| D-50A | 50W | 90~132VAC 180~264VAC | (5V, 12V) | (6A, 2A) | 88% | 159*98*38 |
| D-50B | 50W | 90~132VAC 180~264VAC | (5V, 24V) | (6A, 1A) | 88% | 159*98*38 |
| D-50C | 50W | 90~132VAC 180~264VAC | (12V, 24V) | (2A, 1A) | 88% | 159*98*38 |
| D-50F | 50W | 90~132VAC 180~264VAC | (12V, 12V) | (2A, 2A) | 88% | 159*98*38 |
| D-60A | 60W | 100~120VAC 200~240VAC | (5V, 12V) | (4A, 3A) | 88% | 159*98*38 |
| D-60B | 60W | 90~132VAC 180~264VAC | (5V, 24V) | (3A, 1.8A) | 88% | 159*98*38 |
| D-60C | 60W | 90~132VAC 180~264VAC | (12V, 24V) | (2A, 1.5A) | 88% | 159*98*38 |
| D-75A | 75W | 90~132VAC 180~264VAC | (5V, 12V) | (7A, 3A) | 88% | 159*98*38 |
| D-75B | 75W | 90~132VAC 180~264VAC | (5V, 24V) | (5A, 2A) | 88% | 159*98*38 |
| D-75C | 75W | 90~132VAC 180~264VAC | (12V, 24V) | (2A, 2A) | 88% | 159*98*38 |
| D-75F | 75W | 100~120VAC 200~240VAC | (12V, 12V) | (3A, 3A) | 88% | 159*98*38 |

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE

| MODEL | POWER | INPUT VOLTAGE RANGE | OUTPUT VOLTAGE | OUTPUT CURRENT | EFFCY | SIZE(L*W*H)MM |
|--------|-------|--------------------------|----------------|----------------|-------|---------------|
| D-100A | 100W | 90~132VAC 180~264VAC | (5V, 12V) | (10A, 4A) | 88% | 199*98*38 |
| D-100B | 100W | 90~132VAC 180~264VAC | (5V, 24V) | (6A, 4A) | 88% | 199*98*38 |
| D-100C | 100W | 90~132VAC 180~264VAC | (12V, 24V) | (4A, 2A) | 88% | 199*98*38 |
| D-120A | 120W | 90~132VAC 180~264VAC | (5V, 12V) | (12A, 5A) | 88% | 199*98*38 |
| D-120B | 120W | 90~132VAC 180~264VAC | (5V, 24V) | (6A, 4A) | 88% | 199*98*38 |
| D-120C | 120W | 90~132VAC 180~264VAC | (12V, 24V) | (3A, 3A) | 88% | 199*98*38 |
| D-150A | 150W | 90~132VAC 180~264VAC | (5V, 12V) | (15A, 6A) | 88% | 199*110*50 |
| D-150B | 150W | 90~132VAC 180~264VAC | (5V, 24V) | (6A, 5A) | 88% | 199*110*50 |
| D-150C | 150W | 90~132VAC 180~264VAC | (12V, 24V) | (6A, 3A) | 88% | 199*110*50 |
| D-150F | 150W | 100~120VAC 200~240VAC | (12V, 12V) | (6A, 6A) | 88% | 199*110*50 |
| D-150F | 150W | 100~120VAC 200~240VAC | (24V, 24V) | (3A, 3A) | 88% | 199*110*50 |
| D-200A | 200W | 90~132VAC 180~264VAC | (5V, 12V) | (12A, 10A) | 88% | 199*110*50 |
| D-200B | 200W | 90~132VAC 180~264VAC | (5V, 24V) | (10A, 6A) | 88% | 199*110*50 |
| D-200C | 200W | 100~120VAC 200~240VAC | (12V, 24V) | (5A, 6A) | 88% | 199*110*50 |
| D-350A | 350W | 90~132VAC 180~264VAC | (5V, 12V) | (20A, 20A) | 88% | 215*115*50 |
| D-350B | 350W | 90~132VAC 180~264VAC | (5V, 24V) | (20A, 10A) | 88% | 215*115*50 |
| D-350C | 350W | 90~132VAC 180~264VAC | (12V, 24V) | (10A, 10A) | 88% | 215*115*50 |

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE

