

MS Series Power Supply



PRODUCT FEATURES

- ▶ Full range AC voltage input
- ▶ The efficiency reaches 88% at full load (230 V)
- ▶ LED start indicator
- ▶ Low standby power consumption, less than 0.3W
- ▶ Protection type: short circuit protection/overload protection/overvoltage protection
- ▶ The working temperature can be as high as 70°C
- ▶ Natural air cooling / Fan Cooling
- ▶ Small size, aluminum shell
- ▶ Full load aging test at 100% ambient temperature of 50°C
- ▶ Can be operated at an altitude of 2000 kilometers
- ▶ CE, ROHS FCC and other certifications.
- ▶ The output below 5V (including 5V) is synchronous

USAGE SCENARIO

- ▶ Electronic/scientific research instruments, industrial control equipment, camera monitoring equipment, medical equipment, lighting equipment, automation equipment, etc

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
MS-15	15W	90-264VAC	5V / 12V / 24V	3A / 1.3A / 0.6A	88%	85*58*30
MS-25	25W	90-264VAC	5V / 12V / 24V	5A / 2A / 1A	88%	85*58*30
MS-35	35W	90-264VAC	5V / 12V / 24V	7A / 3A / 1.5A	88%	85*58*30
MS-50	50W	90-264VAC	5V / 12V / 24V	10A / 4.2A / 2.1A	88%	110*78*35
MS-60	60W	90-264VAC	5V / 12V / 24V	12A / 5A / 2.5A	88%	110*78*35
MS-75	75W	90-264VAC	12V / 24V	6.3A / 3.2A	88%	110*78*35
MS-100	100W	90-264VAC	12V / 24V	8.5A / 4.5A	88%	159*98*40
MS-120	120W	90-264VAC	12V / 24V	10A / 5A	88%	159*98*40
MS-150	150W	90-264VAC	12V / 24V	12.5A / 6.5A	88%	159*98*40
MS-250	250W	100-120VAC 200-240VAC	12V / 24V	20A / 10A	88%	215*115*50
MS-500	500W	100-120VAC 200-240VAC	12V / 24V	40A / 20A	88%	215*115*50

The final parameters and specifications shall be subject to the Product Specification provided by our company



PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
MS-700	700W	200-240VAC	12V / 24V / 36V / 48V	58A / 29A / 19A / 14.5A	88%	238*124*65
MS-800	800W	200-240VAC	12V / 24V / 36V / 48V	67A / 33A / 22A / 17A	88%	238*124*65
MS-1000	1000W	200-240VAC	12V / 24V / 36V / 48V	83A / 42A / 28A / 21A	88%	238*124*65
MS-1200	1200W	200-240VAC	12V / 24V / 36V / 48V	100A / 50A / 33A / 25A	88%	238*124*65
MS-1500	1500W	200-240VAC	12V / 24V / 36V / 48V	125A / 62.5A / 42A / 31A	88%	238*124*65

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE

