



NDR, EDR, MDR Rail Type Power Supply



PRODUCT FEATURES

- ▶ Full range AC voltage input
- ▶ Protection type: short circuit protection/overload protection/overvoltage protection
- ▶ Full load aging test at 100% ambient temperature of 50°C
- ▶ The efficiency reaches 88% at full load (230 V)
- ▶ The working temperature can be as high as 70°C
- ▶ Natural air cooling
- ▶ LED start indicator
- ▶ Can be operated at an altitude of 2000 kilometers
- ▶ CE, ROHS, FCC and other certifications.
- ▶ Low standby power consumption, less than 0.2W
- ▶ Small size, convenient installation of guide rail
- ▶ The output below 5V (including 5V) is synchronous rectifier

USAGE SCENARIO

- ▶ Electronic/scientific research instruments, industrial control equipment, camera monitoring equipment, medical equipment, lighting equipment, automation equipment, etc

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
NDR-75	75W	100-240VAC	12V / 24V	6.3A / 3.2A	88%	32*125*100
NDR-120	120W	100-240VAC	12V / 24V	10A / 5A	88%	40*125*113.5
NDR-150	150W	100-240VAC	12V / 24V	12.5A / 6.5	88%	40*125*113.5
NDR-240	240W	100-240VAC	12V / 24V / 48V	20A / 10A / 5A	88%	63*125*113.5
NDR-480	480W	100-240VAC	12V / 24V / 48V	40A / 20A / 10A	88%	125*125*100
EDR-75	75W	100-240VAC	12V / 24V	6A / 3.2A	88%	32*125*100
EDR-120	120W	100-240VAC	12V / 24V	10A / 5A	88%	40*125*113.5
EDR-150	150W	100-240VAC	12V / 24V	12.5A / 6.5A	88%	40*125*113.5
EDR-240	240W	100-240VAC	12V / 24V	20A / 10A	88%	63*125*113.5
MDR-20	20W	100-240VAC	12V / 24V	1.67A / 1A	88%	22.5*90*100
MDR-40	40W	100-240VAC	12V / 24V	3.3A / 1.7A	88%	40*90*100
MDR-60	60W	100-240VAC	12V / 24V	5A / 2.5A	88%	40*90*100

The final parameters and specifications shall be subject to the Product Specification provided by our company



NDR, EDR, MDR Rail Type Power Supply

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
MDR-100	100W	100-240VAC	12V / 24V	7.5A / 4A	88%	40*90*100

The final parameters and specifications shall be subject to the Product Specification provided by our company

PRODUCT SELECTION TABLE



NDR-75, NDR-120

NDR-240

NDR-480

EDR-150

MDR-20

MDR-40, MDR-60

MDR-60