



PRODUCT FEATURES

- ▶ Full range AC voltage input
- ▶ The efficiency reaches 88% at full load (230 V)
- ▶ LED start indicator
- ▶ Low standby power consumption, less than 0.3W
- ▶ Protection type: short circuit protection/overload protection/overvoltage protection
- ▶ The working temperature can be as high as 70°C
- ▶ Natural air cooling/ Fan Cooling
- ▶ Small size, aluminum cooling shell
- ▶ Full load aging test at 100% ambient temperature of 50°C
- ▶ Can be operated at an altitude of 2000 kilometers
- ▶ CB, CE, ROHS FCC and other certifications.
- ▶ The output below 5V (including 5V) is synchronous

USAGE SCENARIO

- ▶ Electronic/scientific research instruments, industrial control equipment, camera monitoring equipment, medical equipment, lighting equipment, automation equipment, etc

PRODUCT SELECTION TABLE

MODEL	POWER	INPUT VOLTAGE RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	EFFCY	SIZE(L*W*H)MM
S ₂ -1000	1000W	200-240VAC	12V / 24V / 36V / 48V / 60V	75A / 45A / 28A / 21A / 16.7A	88%	239*130*65
S ₂ -1200	1200W	200-240VAC	12V / 24V / 36V / 48V / 60V	88A / 50A / 33A / 25A / 20A	88%	239*130*65
S ₂ -1500	1500W	200-240VAC	12V / 24V / 36V / 48V / 60V	115A / 62.5A / 42A / 31A / 25A	88%	270*154*70
S ₂ -2000	2000W	200-240VAC	12V / 24V / 36V / 48V / 60V	150A / 83A / 56A / 42A / 33A	88%	270*154*70
S ₂ -2500	2500W	200-240VAC	12V / 24V / 36V / 48V / 60V	208A / 104A / 69.5A / 52A / 41.6A	88%	285*186*70
S ₂ -3000	3000W	200-240VAC	12V / 24V / 36V / 48V / 60V	210A / 125A / 83A / 62.5A / 50A	88%	285*186*70
S ₂ -4000	4000W	200-240VAC	12V / 24V / 36V / 48V / 60V	280A / 166A / 111A / 83A / 67A	88%	359*215*70
S ₂ -5000	5000W	200-240VAC	12V / 24V / 36V / 48V / 60V	340A / 208A / 138.8A / 104A / 83A	88%	359*215*70
S ₂ -6000	6000W	200-240VAC	12V / 24V / 36V / 48V / 60V	500A / 250A / 166.6A / 125A / 100A	88%	374*190*150
S ₂ -8000	8000W	200-240VAC	12V / 24V / 36V / 48V / 60V	666.6A / 333.3A / 222.2A / 166.6A / 133.3A	88%	374*190*150
S ₂ -10000	10000W	200-240VAC	24V / 36V / 48V / 60V	417A / 278A / 208A / 167A	88%	450*223*175

PRODUCT SELECTION TABLE



The final parameters and specifications shall be subject to the Product Specification provided by our company