



<b>Checked by</b>	<b>Rechecked by</b>	<b>Approved by</b>
<b>Comments</b>	<b>Approved by</b>	<b>Company's seal</b>
<b>Customer's Name:</b>		

Please send the original back to us after you have approved and signed.

#### Modify History

<b>Ver.</b>	<b>Page</b>	<b>Revised Descriptions</b>	<b>Date</b>	<b>Revision</b>	<b>Approval</b>
REV.1.0	ALL	TO	2025.05.16		

# Product Parameter:

58.5"		Specifications	Units/Number	Notes
Model				
	Dimension	1465(H)×439 (V)×60W)	MM	
	Shell material	white	-	
	Gross Weight	/	Kg/gross	
Screen Parameters	Display Size	1428.48(H)×401.76(V)	MM	
	Display- resolution	3840*1080	Pixel	
	Brightness	400	Cd/m <sup>2</sup>	
	Contrast ratio	1300: 1	-	
	Display scale	16:4.5	-	
	Viewing angle	89/89/89/89	-	
	Pixel pitch	0.372 × 0.372	MM	
	Display color	1.07	B	
Electrical	Maximum power	≤160	W	
	Standby power	≤1	W	
	Supply Voltage	12V	V	
	Horn	8 Ω 3W*2	-	
WorkStorage	Operating temperature	0-50	°C	
	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	°C	
	Storage Humidity	10%~80%	%hr	
Power interface		AC 110-240V		

Model		58.5"	Specifications	Units/Number	Notes
Functional configuration	CPU		The quad-core 64-bit Cortex-A55 has a maximum frequency of 2.0GHz		
	Operating System		Android 11.0		
	Memory Storage		Standard 8G		
	built-inROM		/		
	HDMI Out		HDMI2.0 supports up to 4K@60HZ output		
	HDMI import		/		
	Support Video-Formats		Support wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc		
	Support Image-Formats		Supports BMP, JPEG, PNG, GIF		
	Audio Input/Output		Supports a speaker interface, up to one 8Ω 5W Dual-channel speaker output		
	Headphone Output		Standard 3.5mm, 4 section earphone headset base, CTIA (US standard) standard		
	USB Interface		1 *USB3.0 host, 1*USB3.0_OTG		
	Serial Port		4 TTL serial ports (1 optional TTL/RS232/RS485,3 optional TTL/RS232), one of which is a debugging serial port		
	Network Support		Supports 1000M/100M adaptive Ethernet and WIFI-2.4G BT-4.1 4G module interface		
	Memory Card		/		
	RTC		/		
System Upgrade		Supports local USB upgrades			

# Product Rendering:



