



<b>Checked by</b>	<b>Rechecked by</b>	<b>Approved by</b>
<b>Comments</b>	<b>Approved by</b>	<b>Company's seal</b>
<b>Customer's Name:</b>		

Please send the original back to us after you have approved and signed.

#### Modify History

<b>Ver.</b>	<b>Page</b>	<b>Revised Descriptions</b>	<b>Date</b>	<b>Revision</b>	<b>Approval</b>
REV.1.0	ALL	TO	2025.05.16		

# Product Parameter:

67.5"		Specifications	Units/Number	Notes
Model				
	Dimension	1686.5(H)×500 (V)×60(W)	MM	
	Shell material	white	-	
	Gross Weight	/	Kg/gross	
Screen Parameters	Display Size	1649.66(H)×463.97(V)	MM	
	Display- resolution	3840*1080	Pixel	
	Brightness	400	Cd/m <sup>2</sup>	
	Contrast ratio	1400: 1	-	
	Display scale	16:4.5	-	
	Viewing angle	89/89/89/89	-	
	Pixel pitch	0.4296×0.4296	MM	
	Display color	1.07	B	
Electrical	Maximum power	≤220	W	
	Standby power	≤1	W	
	Supply Voltage	12V	V	
	Horn	8 Ω 3W*2	-	
WorkStorage	Operating temperature	0-50	°C	
	Working- humidity	10%~80%	%hr	
	Storage temperature	-20-50	°C	
	Storage Humidity	10%~80%	%hr	
Power interface		AC 110-240V		

<b>67.5"</b>		<b>Specifications</b>	Units/N umber	Notes
<b>Model</b>				
<b>Functional configuration</b>	<b>CPU</b>	The quad-core 64-bit Cortex-A55 has a maximum frequency of 2.0GHz		
	<b>Operating System</b>	Android 11.0		
	<b>Memory Storage</b>	Standard 8G		
	<b>built-inROM</b>	/		
	<b>HDMI Out</b>	HDMI2.0 supports up to 4K@60HZ output		
	<b>HDMI import</b>	/		
	<b>Support Video-Formats</b>	Support wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc		
	<b>Support Image-Formats</b>	Supports BMP, JPEG, PNG, GIF		
	<b>Audio Input/Output</b>	Supports a speaker interface, up to one 8Ω 5W Dual-channel speaker output		
	<b>Headphone Output</b>	Standard 3.5mm, 4 section earphone headset base, CTIA (US standard) standard		
	<b>USB Interface</b>	1 *USB3.0 host, 1*USB3.0_OTG		
	<b>Serial Port</b>	4 TTL serial ports (1 optional TTL/RS232/RS485,3 optional TTL/RS232), one of which is a debugging serial port		
	<b>Network Support</b>	Supports 1000M/100M adaptive Ethernet and WIFI-2.4G BT-4.1 4G module interface		
	<b>Memory Card</b>	/		
	<b>RTC</b>	/		
<b>System Upgrade</b>	Supports local USB upgrades			

# Product Rendering:



